Swedish One-Man Saws

From the Article in "Skogen," May 1926,
By MR. GUSTAF LUNDBERG.

In Swedish logging, especially in the northern and middle parts of the country, the old-fashioned two-man saw has been almost entirely superseded by the one-man saw, with which most of the cutting is now done.

The reason for this is that the average size of the trees cut has been getting smaller, and the single saw—the one-man saw—has been improved continually and has now attained perfection. Thus, two cutters, each working alone with single saws in a forest of ordinary sized trees, actually are doing better work than two men working together with a double saw.

There is also a matter of psychology—two workers would rather work singly than together. A man working alone and getting the profit of his work himself, is

Fig. 1. The Kompisapparat used for cutting down trees.

anxious to do his best, since he gets the whole profit of his work, rather than eventually having to divide it with his companion. Thus, as the single saw is more widely used, not only is the amount of work done increased, but the working intensity is also increased.

The improvement in efficiency of the single saw has consisted chiefly in making more suitable teeth for the saw—irregular teeth with cutting edges suited to one-way cutting blades; with height of the teeth and distance between them properly gauged; and also in making the saw blade thinner and more elastic. It has been proved in practice as well as in theory that the thinner the blade is, the greater the cutting force of the saw, as long as the firmness of the blade and cutting faces is maintained.

By making the blade thinner at the back than at the cutting edge—known as thin-backed saws—it has been possible to reduce the setting, without diminishing the free run of the blade. Hereby the efficiency is increased, and the cut is better the less set the teeth are, as long as the blade runs free and there is no side-friction.

It must be noted that the making of thinner saw blades has only been possible through steady improvement of the quality of steel used. The modern single saw, which experienced wood workers prefer, is how-

ever, often so thin that much skill is required for using it without risk of breaking it by wrong handling.

With the "Sandvikers Kompisapparat," it has been possible to use a thin blade with all its advantages in increased efficiency, without the risk of breaking the blade. It is also possible to use a longer blade, giving a larger and more effective cutting surface and more effective incision than is produced with the ordinary single saw.

This is a simple mechanism consisting of a spiral spring, fastened to the end of the sawblade, which during the sawing keeps the blade in even tension and makes the guiding of the saw easier and gives a better cut as well. The apparatus consists of two steel tubes of oval cross section, light and strong and fitting into each other. This double tube is finished at both ends with claws to make it easier to fasten it to the ground and to the tree. On the tube is placed an arm, adjustable in different directions, to which the spiral spring is fastened. This arm can be adjusted by hand, without any screwing, to the desired height. The whole apparatus weighs six and one-half pounds. It can be

Fig. 2. The Kompisapparat used for cutting up logs.

used equally well for cutting up trees into logs or for cutting down trees, and can saw upwards as well as down.

With the "Apparat" are used special saws, of which the standard model is a single saw with a thin back straight teeth, finely tapered and with a distance between the bases of the teeth known as P teething. The more important measures are as follows: Thickness of the blade, .043" at the edge and about .025" at the back; length of blade 3'9", width 2 3/4"; distance between the points of the teeth .4", between the base .2"; the angles of the teeth (the angles of the edge against the bases of the teeth) 71° to 72°, setting .006" the angles of the cutting face of the teeth 58°. This saw, however, is only made for use in connection with this apparatus.

Extensive experiments have been carried on at the College of Forestry in Sweden, during 1925 and 1926 with the Kompisapparat and special saws, to determine the worth of the apparatus, and particularly to determine the best type of blade. These experiments were commenced in June, 1925, at Malingsbo as a temporary undertaking, exhibiting the apparatus in action. In the following November, near Garpenberg, systematic tests were made with different types of saw blades.

Fig. 4. Curves showing the result of cutting down trees at Garpenberg, 1925.

Fig. 5. Curves showing results with different saws used with the Kompis apparatus during cutting operations at Lidings, 1926.

In January, 1926, further experiments with definite standardised models of the apparatus were made at the large logging operations at Lidingö. The result of these experiments can be summed up as follows:

After several trials a standard model of the apparatus was decided upon—well-balanced in its details, strong and very serviceable and giving complete satisfaction. The only part which requires, after a reasonable time, to be renewed is the spring, but this is to be expected and is easily done. On account of its light weight, the apparatus can be carried by the cutter without inconvenience; and it is very simple and easy to set up for work.

For cutting down trees, especially of average or large size, it is most useful, as well for increasing efficiency in sawing as for making the work easier for the men. In Fig. 4 are recorded some of the curves showing the working results for the Garpenberg experiments, in connection with the saws of Type XII N and 25.

The XII N saw is a common single saw of a 1924 model, which has been used with and without the new apparatus. The horizontal lines give the area and diameter of the sawed trees, and the vertical lines the time it took to saw the respective trunks.

On account of forced sawing during this experiment, the results show as higher than normal. It is noticeable, however, that the same saw used with the apparatus shows about double the sawing effect than when used in the ordinary way for which this saw is intended, on account of the regulating influence of the spiral spring on the blade, and the consequent better steering, saw-log through a diameter of twelve inches.

In addition to this must be counted the greater effect which it is possible to obtain with the use of a thinner and longer sawblade (entailing less friction and a larger cutting area); everyone will therefore realize that considerable work is saved and better results obtained with a special blade.

In Figure 5 are given sawing times for different dimensions, and a number of special blades, as used in the last experiments at Lidingö, where all the sawing was done with the "Kompisapparat."

It is to be noted that these times, unlike the figures in Figure 4, were obtained by steady, regular work done by experienced woodworkers, and thus can be regarded as normal results for log sawing in a temperature of 10 or 15 degrees (Réaumur)—about 40°F.

As a comparison, saw No. 25 was used in both the experiments. Saw No. 23 in Figure 5 is the one already described, which is accepted as the standard model of this apparatus.

For sawing felled trees, the saving in effort by using the apparatus is not so striking, but, particularly for average and large sizes, the trouble of placing the apparatus is highly rewarded. Therefore, even if the advantage is slight in comparison with that in using for standing trees, the apparatus is well worth while.

From these extensive experiments and observations it may be concluded that the apparatus is an important invention which should be popular with wood workers. It can now be obtained from the factory, address Sandvikens Jernverks A.-B., Sandviken, Sweden. The price of the apparatus with the special saw is approximately \$5.60, an extra saw without handle is \$1.15, and extra spring 50c.

Impressions of the World's Forestry Conference

By P. Z. CAVERHILL, CHIEF FORESTER OF
BRITISH COLUMBIA

The World's Forestry Conference, held at Rome, April 29 to May 5, 1926, was described by C. S. Dana, of the American Forestry Association and head of the American delegation to the conference, as "The greatest gathering of foresters that has ever met." Delegates came from more than 50 countries, speaking many different languages; yes, even thinking in entirely different ways—their thoughts influenced largely by the development and economic conditions of the community from which they had come. Thus, the forester from southern Europe includes in his forest estimates all material, even to branchwood and twigs, and these are sold for fagots or for other uses, returning a considerable revenue; the northern foresters include stem and bark, but not branchwood; the American only that portion of stem that can be manufactured to a four-inch top in the East or to a 12 to 14-inch top on the Pacific Coast.

It is only after the most careful study of the vast amount of material included in the proceedings, covering 3500 pages, that one dare draw any definite conclusions from the work accomplished there. It seems, however, that the most important step taken at the conference was the recommendation for the establishment

of a bureau for collecting and disseminating world forest statistics. The importance of this work is further emphasized by visiting the many forests of Europe, viewing their choice bits of forest, and being told that this or that area contains 700 or 800 cubic meters per hectare, which, after calculating for deduction in bark and branchwood, is equivalent to 1000 board feet per acre. We had seen many similar acres in the Rocky Mountain region cruised at 15 to 20,000 board feet. Even traveling for a few more days, stopping a day or two here and a day there, does not give one sufficient data to form definite conclusions. Impressions are formed however, and it is these personal impressions that I give in reply to your inquiry regarding forest conditions in Europe.

The Timber Supply of Europe

Since the war the European cut is increasing and will during the next few decades furnish more wood material than ever before. In southern Europe many years prior to the war the cut was regulated on a very conservative basis. If the growth was estimated at 10 cubic meters per hectare, the cut was restricted to nine, the balance going to increase the forest capital. Now, due to many causes, the process